

 **everwell**<sup>®</sup>




**R22** /  **R410A**  
REFRIGERANT




**FLOOR & CEILING UNIT - FCA SERIES**

# Floor & Ceiling Unit - FCA Series



**1. Flexible Installation**, ceiling suspended and floor standing.




**4. LED Display**, more intuitive, and simple error code shown in display.



**2. Easy Convenient Installation and Maintenance**, washable filter design.



**5. New Upper and Lower Buckle Type Wheel Case**, can be removed alone, which is convenient to adjust the wheel motor.



**3. Auto-Swing Function**, built-in two louver motor, vertical and horizontal air-flow adjustment.

Model			FCA-18	FCA-24	FCA-36	FCA-48	FCA-60
Power Supply		V/Hz/Ph	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1	208-230/60/1
Capacity							
Cooling Capacity	Capacity	Btu/h	18000	24000	36000	48000	60000
		RT	1.5	2	3	4	5
Physical Data							
Air Flow Volume (Hi/Med/Low)		CFM	450/330/210	880/760/640	880/760/640	1230/1110/1000	1230/1110/1000
Noise Level (Hi/Med/Low)		dB(A)	50/48/45	50/48/45	50/48/45	57/54/51	56/54/48
Net Dimension (WxHxD)		Inches	34 5/8"x26 3/4"x8 7/8"	49"x26 3/4"x8 7/8"	49"x26 3/4"x8 7/8"	65 3/4"x26 3/4"x9 5/8"	65 3/4"x26 3/4"x9 5/8"
Packing Dimension (WxHxD)		Inches	37 3/4"x30 1/4"x12 3/4"	52 1/8"x30 1/4"x12 3/4"	52 1/8"x30 1/4"x12 3/4"	68 7/8"x30 1/4"x12 3/4"	68 7/8"x30 1/4"x12 3/4"
Net Weight		Lbs	66	77	77	103	103
Gross Weight		Lbs	77	90	90	119	119
Applicable Area		m2	20-35	28-50	42-70	56-93	70-107
Piping Data							
Piping Size	Liquid	Inches	1/4"	3/8"	3/8"	3/8"	3/8"
	Gas	Inches	1/2"	5/8"	3/4"	3/4"	3/4"
	Drainage	Inches	1"	1"	1"	1"	1"
Loading							
Loading Qty (20' / 40' / 40' HQ)		Pcs	115/250/320	70/162/162	70/162/162	65/135/150	65/135/150



Distributed by \_\_\_\_\_